



CROWN VIC/GRAND MARQUIS 2024 TECHNICAL RULEBOOK

BODY:

- A. FRONT AND REAR BUMPER MUST REMAIN STOCK WITH NO SHARP EDGES. BUMPERS MUST HAVE TOW CHAINS FRONT AND REAR.
- B. NO PUSH BARS IN FRONT OR REAR OF CAR.
- C. HOOD AND TRUNK MAY UTILIZE STOCK HINGES, BUT MUST BE SECURED WITH HOOD PINS.
- D. NO HULLING OR LIGHTENING OF BODY. THE ONLY AREAS ON CAR.
- E. THAT MAY BE HULLED ARE THE FRONT DRIVER AND PASSENGER DOORS.
- F. ALL FLAMMABLE MATERIALS AND GLASS MUST BE REMOVED.
- G. ANY HOLES IN FRONT FIREWALL AND REAR FIREWALL MUST BE COVERED WITH ALUMINUM OR STEEL.
- H. ALL CARS MUST HAVE NUMBERS ON FRONT DOORS AND ROOF.
- I. STEERING COLUMN MUST REMAIN STOCK, ALL AIRBAGS MUST BE REMOVED. QUICK RELEASE STEERING WHEEL OK, BUT MUST BE MOUNTED TO STOCK STEERING COLUMN.
- J. MUST HAVE AT LEAST 4 VERTICAL WINDSHIELD BARS IN FRONT OF DRIVER.
- K. ROLL CAGE MUST BE INSIDE DRIVER COMPARTMENT ONLY, NO PART OF CAGE MAY EXTEND OUTSIDE OF PASSENGER COMPARTMENT.
- L. MUST HAVE STOCK DASH IN PLACE.
- M. FOUR DRIVER DOOR BARS AND 3 PASSENGER DOOR BARS MINIMUM.
- N. CAGE MUST BE SECURELY MOUNTED TO FRAME SUSPENSION.
- O. NO ALTERING OF STOCK SUSPENSION.

ENGINE/ TRANSMISSION:

- A. ENGINE MUST BE COMPLETELY STOCK.
- B. 4.6 SOHC
- C. MUST HAVE MUFFLERS.
- D. EXHAUST MUST EXTEND TO REAR TIRES.

- E. CATALYTIC CONVERTOR MAY BE REMOVED.
- F. TRANSMISSION MUST BE COMPLETELY STOCK.
- G. A.C. CONDENSER MUST BE REMOVED.

SAFETY:

- A. DRIVERS MUST WEAR FULL FIRE SUIT, RACING GLOVES, RACING SHOES AND HELMET WHILE ON TRACK.
- B. HANS DEVICE RECOMMEND.
- C. RACING SEAT AND BELTS MANDATORY.
- D. RACING BELT MUST HAVE 5 POINT SYSTEM.
- E. FIRE EXTINGUISHER REQUIRED IN ALL CARS.
- F. BATTERY MAY BE IN STOCK LOCATION OR RELOCATED TO TRUCK, NO BATTERIES INSIDE COCKPIT/PASSENGER COMPARTMENT.
- G. BATTERY DISCONNECT SWITCH ON THE DRIVER SIDE, REAR SPEAKER AREA.

TIRES/WHEELS:

- A. TIRES MUST BE DOT LEGAL AND ALL 4 TIRES MUST BE THE SAME SIZE.
- B. WHEELS MUST BE STOCK STEEL AND ALL 4 WHEELS MUST BE SAME SIZE AND OFFSET.
- C. NO WHEEL SPACERS OF ANY KIND.

WEIGHT:

- A. NO ADDING BALLAST OF ANY TYPE TO CAR.

BRAKES:

- A. MUST REMAIN FACTORY STOCK, ALL 4 CORNERS MUST BE OPERABLE.

REAR END:

- A. MUST BE FACTORY STOCK REAR END WITH STOCK COMPONENTS.
- B. THE ONLY LEGAL GEARS WILL BE 2.73, 3.27, AND 3.55.
- C. REAR DIFFERENTIAL MAY BE LOCKED BY ANY MEANS NECESSARY, BUT GEAR RATIO RULE REMAINS THE SAME (3.55 MAX GEAR).

FUEL:

- A. PUMP GAS ONLY, NO RACING FUEL.
- B. STOCK FUEL TANK AND FUEL PUMP ONLY.

THE ABSENCE OF A SPECIFIC RULE DOES NOT IMPLY APPROVAL, CONSENT OR PERMISSION REGARDING THAT SUBJECT. ANY QUESTIONS OR DOUBTS REGARDING SUCH MATTERS SHOULD BE DIRECTED TO TRACK OFFICIALS FOR A CLARIFICATION.